AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (currently amended): A method of manufacturing a solar battery by electrically connecting a plurality of cells to one another using connection members, comprising:

a flux applying step of applying a flux to [[the]] surfaces of the cells;

a disposing step of disposing the connection members over the adjacent cells to which the flux has been applied;

a string step of connecting the connection members to the cells by soldering; and a cell heating step of heating the cells connected to the connection members.

Claim 2 (original): The method of manufacturing the solar battery according to claim 1, wherein a heating temperature of the cell heating step is not less than a boiling temperature of the flux.

Claim 3 (original): The method of manufacturing the solar battery according to claim 1, wherein a heating temperature of the cell heating step is not less than an activating temperature of the flux.

U.S. Patent Application Serial No.: 10/594,389 Response/Amendment filed November 16, 2010 Reply to OA dated August 17, 2010

Claim 4 (previously presented): The method of manufacturing the solar battery according to claim 1, wherein in the cell heating step, the heating temperature is +140°C or more and +160°C or less, and a heating time is one minute or more and five minutes or less.

Claim 5 (previously presented): The method of manufacturing the solar battery according to claim 1, wherein in the cell heating step, the heating temperature is +150°C, and the heating time is three minutes.

Claim 6 (withdrawn): The method of manufacturing the solar battery according to claim 1, wherein in the cell heating step, the heating temperature is more than +160°C, and a heating time is less than one minute.

Claim 7 (withdrawn): The method of manufacturing the solar battery according to claim 1, wherein in the cell heating step, the heating temperature is +200°C or more, and the heating time is less than 20 seconds.

Claim 8 (withdrawn): The method of manufacturing the solar battery according to claim 1, wherein in the cell heating step, the heating temperature is +250°C or more, and the heating time is less than ten seconds.

3

Reply to OA dated August 17, 2010

Claim 9 (previously presented): The method of manufacturing the solar battery

according to claim 1, wherein in the cell heating step, the whole cells are heated.

Claim 10 (previously presented): The method of manufacturing the solar battery

according to claim 1, wherein the cell heating step includes: heat release means for preventing a

solder which connects the connection members to the cells from being molten.

Claim 11 (withdrawn): The method of manufacturing the solar battery according to

claim 10, wherein the heat release means is a conveyance belt which conveys the cells and which

comes into contact with at least a connection members portion during the conveyance.

Claim 12 (withdrawn): The method of manufacturing the solar battery according to

claim 11, wherein, in the string step, the conveyance belt does not come into contact with the

connection members portion, and in the cell heating step, the conveyance belt comes into contact

with the connection members portion.

Claim 13 (previously presented): The method of manufacturing the solar battery

according to claim 1, wherein in the string step, hot air is blown against the connection members

to perform the soldering, and in the cell heating step, the cells are irradiated with an infrared ray

to heat.

4